Nο	83,068

PATENT APPLICATION

Navy Case No. 83,068 Inventors: Lyons et al.

CLAIMS

We claim:

1. A process for introducing defects into a metal oxide, said process comprising the steps of:

applying a gas to a sufficient amount of a metal oxide sample to increase the specific energy;

heating said metal oxide sample; and cooling said metal oxide sample.

- 2. The process as in claim 1, further comprising the step of:

 maintaining said heating step at a temperature of from about 300 to about 600 °C.
- 3. The process as in claim 2, wherein said heating step is maintained from about 6 to about 72 hours.
- 4. The process as in claim 1, wherein said gas is applied to said metal oxide sample at a linear flow rate of at least about 50 cm.
- 5. The process as in claim 1, wherein said heating step is from about 2 to about 20 °C/min up to about 460 °C.

Navy Case No. 83,068 Inventors: Lyons et al.

- 6. The process as in claim 5, further comprising the step of:

 maintaining said temperature of about 460 °C for 24 hours.
- 7. The process as in claim 1, wherein said cooling is from about 2 to about 20 °C/min until ambient air temperature is achieved.
- 8. The process as in claim 1, wherein said gas is a mixture of O_2 and $H_2O_{(g)}$.
- 9. The process as in claim 1, wherein said metal oxide sample is V₂O₅.
- 10. The process as in claim 1, wherein said sufficient amount comprises metal oxide comprising a surface area of about 1- 10 square meters.
- 11. A process for preparing a metal oxide for a battery cathode with increased capacity, said process comprising:

applying a mixture of O_2 and H_2O gas to a sufficient amount of a V_2O_5 metal oxide sample at a linear flow rate of about 50 - 350 cm;

heating said metal oxide sample at a temperature of from about 300 to about 600 °C for a time period of from about 6 to about 72 hours; and

cooling said metal oxide sample.





PATENT APPLICATION

Navy Case No. 83,068 Inventors: Lyons et al.

- 12. The product of the process as in claim 11.
- 13. Vanadium oxide with increased ionic defect concentration.
- 14. A metal oxide with increased ionic defect concentration.
- 15. A metal oxide with increased lithium ion capacity.
- 16. A metal oxide with increased specific capacity.